TORQUE SPECIFICATION

SS05H-01

Part tightened	N⋅m	kgf-cm	ft-lbf
Torque converter clutch x Drive plate	41	420	30
Drive plate x Crankshaft	74	750	54
Extension housing x Transmission case	36	370	27
Parking lock pawl bracket x Transmission case	7.4	75	65 in.·lbf
Valve body x Transmission case	10	100	7
Oil strainer x Valve body	5.4	55	48 in.·lbf
Oil pan	4.4	45	39 in.·lbf
Governor body	3.9	40	35 in.·lbf
Oil cooler pipe union nut	34	350	25
Oil cooler elbow	34	350	25
Park/neutral position switch Bolt Nut	5.4 3.9	55 40	48 in.·lbf 35 in.·lbf
Drain plug	20	205	15
Extension housing x Rear mounting insulator	25	260	19
Rear mounting bracket x Rear support member	58	590	43
Rear mounting bracket x Rear mounting insulator	18	185	13
Stiffener plate x Engine	37	380	27
Stiffener x Torque converter clutch housing	37	380	27
Control shaft lever x Control cable	13	130	9
Transmission x Engine	71	730	53
Vehicle speed sensor	16	160	12
Starter x Transmission case	39	400	29

2001 TOYOTA TACOMA (RM835U)

Author: Date: 217